

1. 製法

1.1 溶湯発泡法

- 1) Tao, X. F. et al.: Compressive failure of Al alloy matrix syntactic foams manufactured by melt infiltration, *Mater. Sci. Eng. A*, **549** (2012), 228–232.
- 2) Orbulov, I. N.: Compressive properties of aluminum matrix syntactic foams, *ibid.*, **555** (2012), 52–56.
- 3) Orbulov, I. N. et al.: Compressive characteristics of metal matrix syntactic foams, *Composites A*, **43-4** (2012), 553–561.
- 4) Goel, M. D. et al.: Dynamic compression behavior of cenosphere aluminum alloy syntactic foam, *Mater. Des.*, **42** (2012), 418–423.
- 5) Castro, G. et al.: Synthesis of syntactic steel foam using gravity-fed infiltration, *Mater. Sci. Eng. A*, **553** (2012), 89–95.
- 6) Peroni, L. et al.: Dynamic mechanical behavior of syntactic iron foams with glass microspheres, *ibid.*, **552** (2012), 364–375.

1.2 ロータス金属

- 7) Ide, T. et al.: Fabrication of porous aluminum with directional pores through continuous casting technique, *Metall. Mater. Trans. A*, **43A-13** (2012), 5140–5152.
- 8) Lee, Y. S. et al.: Centrifugal casting for unpressurized fabrication of lotus-type porous copper, *Mater. Lett.*, **78** (2012), 92–94.
- 9) Zahrani, M. M. et al.: Innovative processing of lotus-type porous magnesium through thermal decomposition of wood, *ibid.*, **85** (2012), 14–17.
- 10) Ichikawa, J. et al.: Fabrication of porous aluminum alloy with aligned unidirectional pores by dipping pipes in base metal melt, *Mater. Trans.*, **53-10** (2012), 1790–1794.

1.3 プリカーサ法

- 11) 金武直幸ほか：ポーラスアルミニウム材料，*軽金属*，**62-3** (2012)，122–134.
- 12) 小橋眞ほか：プリカーサ法による超軽量ポーラス金属および高融点化合物のプロセス技術，*素形材*，**53-2** (2012)，8–13.
- 13) Banhart, J. et al.: Recent trends in aluminum foam sandwich technology, *Adv. Eng. Mater.*, **14-12** (2012), 1082–1087.
- 14) 半谷禎彦ほか：摩擦攪拌法による発泡剤不使用 ADC12 ポーラスアルミニウムと緻密鋼材の複合構造部材の作製，*日本金属学会誌*，**76-5** (2012)，349–354.
- 15) Utsunomiya, T. et al.: Relationship between porosity and interface fracture on aluminum foam sandwich with dense steel face sheets fabricated by friction stir processing route, *Mater. Trans.*, **53-9** (2012), 1674–1679.
- 16) Hangai, Y. et al.: Fabrication and tensile tests of aluminum foam sandwich with dense steel face sheets by friction stir processing route, *ibid.*, **53-4** (2012),

584–587.

- 17) 岡野木綿子ほか：金属板とプリカーサの発泡同時接合に及ぼす型拘束条件の影響，第1回ポーラス材料研究討論会概要，(2012)，11.
- 18) 宇都宮登雄ほか：気孔率および気孔形態を傾斜的に変化させた ADC12 ポーラスアルミニウムの作製，*軽金属*，**62-7** (2012)，278–284.
- 19) Hangai, Y. et al.: Fabrication of functionally graded aluminum foam using aluminum alloy die castings by friction stir processing, *Mater. Sci. Eng. A*, **534** (2012), 716–719.
- 20) Hangai, Y. et al.: Nondestructive observation of pore structure deformation behavior of functionally graded aluminum foam by X-ray computed tomography, *ibid.*, **556** (2012), 678–684.
- 21) Kobashi, M. et al.: Effect of heat absorbing powder addition on cell morphology of porous titanium composite manufactured by reactive precursor method, *ibid.*, **556** (2012), 388–394.
- 22) Kobashi, M. et al.: Effect of precursor's composition and thickness on foaming behavior of Al-Ti intermetallics in volume combustion and self-propagating high-temperature synthesis modes, *J. Mater. Sci. Res.*, **1-4** (2012), 1–10.
- 23) Arakawa, Y. et al.: Effect of elemental powder size on foaming behavior of NiTi alloy made by combustion synthesis, *Materials*, **5-7** (2012), 1267–1274.
- 24) Kato, O. et al.: Fabrication of porous Fe/TiB₂ composites by reactive precursor method, *J. Mater. Sci. Res.*, **1-2** (2012), 110–118.

1.4 スペーサ法

- 25) 袴田昌高ほか：スペーサー法による微細孔ポーラス金属の創製と特性評価，*軽金属*，**62-8** (2012)，313–321.
- 26) Hassani, A. et al.: Production of graded aluminum foams via powder space holder technique, *Mater. Des.*, **40** (2012), 510–515.
- 27) Alizadeh, M. et al.: Compressive properties and energy absorption behavior of Al-Al₂O₃ composite foam synthesized by space-holder technique, *Mater. Des.*, **35** (2012), 419–424.
- 28) Hangai, Y. et al.: Friction powder compaction for fabrication of open-cell aluminum foam by the sintering and dissolution process route, *Metall. Mater. Trans. A*, **43-3** (2012), 802–805.
- 29) Bekoz, N. et al.: Effects of carbamide shape and content on processing and properties of steel foams, *J. Mater. Process. Technol.*, **212-10** (2012), 2109–2116.
- 30) Mutlu, I. et al.: Production and aging of highly porous 17-4 PH stainless steel, *J. Porous Mater.*, **19-4** (2012), 433–440.
- 31) Smorygo, O. et al.: High-porosity titanium foams by powder coated space holder compaction method, *Mater. Lett.*, **83** (2012), 17–19.

- 32) Mansourighasri, A. et al.: Processing titanium foams using tapioca starch as a space holder, *J. Mater. Process. Technol.*, **212**-1 (2012), 83–89.
- 33) Li, B. Q. et al.: Effect of microstructure on the tensile property of porous Ti produced by powder metallurgy technique, *Mater. Sci. Eng. A*, **534** (2012) 43–52.
- 34) Dezfuli, S. N. et al.: Fabrication of biocompatible titanium scaffolds using space holder technique, *J. Mater. Sci.-Mater. Med.*, **23**-10 (2012), 2483–2488.
- 35) Fan, X. et al.: Preparation of bioactive TiO film on porous titanium by micro-arc oxidation, *Appl. Surf. Sci.*, **258**-19 (2012), 7584-7588.
- 36) Gao, Z. et al.: Mechanical modulation and bioactive surface modification of porous Ti-10Mo alloy for bone implants, *Mater. Des.*, **42** (2012), 13–20.
- 37) Torres, Y. et al.: Processing and characterization of porous titanium for implants by using NaCl as space holder, *J. Mater. Process. Technol.*, **212**-5 (2012), 1061–1069.
- 38) Ghasemi, A. et al.: Pore control in SMA NiTi scaffolds via space holder usage, *Mater. Sci. Eng. C*, **32**-5 (2012), 1266–1270.
- 39) Monroe, J. A. et al.: Magnetic response of porous NiCoMnSn metamagnetic shape memory alloys fabricated using solid-state replication, *Scr. Mater.*, **67**-1 (2012), 116–119.
- 40) Aydogmus, T. et al.: Superelasticity and compression behavior of porous TiNi alloys produced using Mg spacers, *J. Mech. Behav. Biomed. Mater.*, **15** (2012), 59–69.
- 41) Wang, Q. et al.: Damping behavior of a novel porous CuAlMn shape memory alloy fabricated by sintering-dissolution method, *Phys. Status Solidi A*, **209**-2 (2012), 277–282.
- 42) Jamshidi-Alashti, R. et al.: Producing replicated open-cell aluminum foams by a novel method of melt squeezing procedure, *Mater. Lett.*, **76** (2012), 233–236.
- 43) Young, M. L. et al.: Cast-replicated NiTiCu foams with superelastic properties, *Metall. Mater. Trans. A*, **43**-8 (2012), 2939–2944.
- 44) DeFouw, J. D. et al.: Processing and compressive creep of cast replicated IN792 Ni-base superalloy foams, *Mater. Sci. Eng. A*, **558** (2012), 129–133.
- 45) 清水透: 多様な気孔構造のステンレス鋼発泡体作成とその特性, *素形材*, **53**-2 (2012), 41–46.
- 46) Shimizu T., et al.: Production of high porosity metal foams using EPS beads as space holders, *Mater. Sci. Eng. A*, **558** (2012), 343–348.
- 47) 岸本哲: ポリマーやセラミックスを内包するセル構造金属材料の創製とその特性, *素形材*, **53**-2 (2012), 30–35.

1.5 MHS 成形体

- 48) 吉村英徳ほか: 鈴形 MHS 成形体およびその外套

材の製造法と機械特性, 平 24 塑加春講論, (2012), 363–364.

2. ポーラス材料の 2 次加工

2.1 二次塑性加工

- 49) Tsuruoka, H. et al., Rolling Characteristics of Porous Aluminum, *Steel Res. Int. Special Edition*, (2012), 103–106.
- 50) Koriyama, S. et al.: Enhancement of the hardness of lotus-type porous copper by shot peening, *ibid.*, (2012), 1215–1218.
- 51) Lobos, J. et al.: Strengthening of lotus-type porous copper by ECAE process, *J. Mater. Process. Technol.*, **212**-10 (2012), 2007–2011.
- 52) 松本良ほか: 摩擦攪拌インクリメンタルフォーミング法によるアルポラスへのスキン層形成, 日本機械学会第 20 回機械材料・材料加工技術講演会 (M&P2012) CD-ROM 論文集, (2012), 講演番号 315.
- 53) Shiomi, M. et al.: Molding of aluminum foams by using hot powder extrusion, *Metals*, **2**-2 (2012), 136–142.
- 54) 塩見誠規ほか: 発泡アルミニウムの回転金型への充填, 平 24 塑加春講論, (2012), 373–374.

2.2 熱処理・溶接

- 55) Chen-Wiegart, Y. K. et al.: Structural evolution of nanoporous gold during thermal coarsening, *Acta Mater.*, **60**-12 (2012), 4972–4981.
- 56) Huang, Y. et al.: Fluxless soldering with surface abrasion for joining metal foams, *Mater. Sci. Eng. A*, **552** (2012), 283–287.
- 57) D’Urso, G. et al.: The formability of aluminum foam sandwich panels, *Int. J. Mater. Form.*, **5**-3 (2012), 243–257.

3. 材料特性

3.1 強度評価

- 58) Zhou, Y. et al.: Manufacture, structure and properties of copper foams, *Chinese J. Rare Metals*, **36**-6 (2012), 889-892.
- 59) Liu, P. S. et al.: Investigation on fatigue property of three dimensional reticulate porous metal foams, *Mater. Sci. Technol.*, **28**-5 (2012), 569–575.
- 60) 齊藤雅樹ほか: 摩擦熱を利用したポーラスアルミニウムコア中空パイプの作製とその圧縮特性, 平 24 塑加春講論, (2012), 369–370.
- 61) 関戸健治ほか: ポーラス Zn-22Al 合金の高温変形挙動に及ぼす気孔率の影響, 同上, (2012), 375–376.
- 62) 小橋真ほか: シンタクティックフォーム/Al フォーム複合材料の作製と内部応力解析, 同上, (2012), 371–372.
- 63) 吉村英徳ほか: 串団子状の中空金属集合体の製造法 (第 6 報), 同上, (2012), 361–362.
- 64) Liu, Y. et al.: Gradient design of metal hollow sphere (MHS) foams with density gradients, *Composites B*, **43**-3 (2012), 1346–1352.

3.2 力学モデリング・シミュレーション

- 65) Karagiozova, D. et al.: Propagation of compaction waves in metal foams exhibiting strain hardening, *Int. J. Solids Struct.*, **49-19** (2012), 2763–2777.
- 66) Nian, W. et al.: Dynamic compaction of foam under blast loading considering fluid-structure interaction effects, *Int. J. Impact Eng.*, **50** (2012), 29–39.
- 67) Cho, J. U. et al.: Impact fracture behavior at the material of aluminum foam, *Mater. Sci. Eng. A*, **539** (2012), 250–258.
- 68) Vesenjak, M. et al.: Analysis of anisotropy and strain rate sensitivity of open-cell metal foam, *ibid.*, **541** (2012), 105–109.
- 69) Burtreau, A. et al.: Impact of material processing and deformation on cell morphology and mechanical behavior of polyurethane and nickel foams, *Int. J. Solids Struct.*, **49-19** (2012), 2714–2732.
- 70) Li, P. et al.: Finite element modelling of the mechanism of deformation and failure in metallic thin-walled hollow spheres under dynamic compression, *Mech. Mater.*, **54** (2012), 43–54.
- 71) Redenbach, C. et al.: Laguerre tessellations for elastic stiffness simulations of closed foams with strongly varying cell sizes, *Int. J. Eng. Sci.*, **50-1** (2012), 70–78.
- 72) Hohe, J. et al.: Numerical and experimental design of graded cellular sandwich cores for multi-functional aerospace applications, *Mater. Des.*, **39** (2012), 20–39.
- 73) Nassar, H. et al.: On the gas pressure forming of aluminium foam sandwich panels: Experiments and numerical simulations, *CIRP Ann-Manuf. Technol.*, **61-1** (2012), 243–246.
- 74) Fan, Z. et al.: Axisymmetric plastic expansion of a cylindrical hole in isotropic metallic foam, *Int. J. Mech. Sci.*, **64-1** (2012), 165–173.
- 75) Del Piero, G., Pampolini, G.: The influence of viscosity on the response of open-cell polymeric foams in uniaxial compression: Experiments and theoretical model, *Continuum Mech. Thermodyn.*, **24-3** (2012), 181–199.
- 76) Souffrant, R. et al.: Advanced material modelling in numerical simulation of primary acetabular press-fit cup stability, *Comput. Methods Biomech. Biomed. Eng.*, **15-8** (2012), 787–793.
- 77) Briody, C. et al.: The implementation of a visco-hyperelastic numerical material model for simulating the behavior of polymer foam materials, *Comput. Mater. Sci.*, **64** (2012), 47–51.
- 78) Yu, M. et al.: Experimental study and numerical prediction of tensile strength properties and failure modes of hollow spheres filled syntactic foams, *ibid.*, **63** (2012), 232–243.
- 79) Yu, M. et al.: Global sensitivity analysis for the elastic properties of hollow spheres filled syntactic foams

using high dimensional model representation method, *ibid.*, **61** (2012), 89–98.

3.3 その他の特性

- 80) Smith, G. H. et al.: Steel foam for structure: A review of application, manufacturing and material properties, *J. Constr. Steel Res.*, **71** (2012), 1–10.
- 81) Yuan, W. et al.: Porous metal materials for polymer electrolyte membrane fuel cell – A review, *Appl. Energy*, **94** (2012), 309–329.
- 82) Zhao, C. Y.: Review on thermal transport in high porosity cellular metal foams with open cells, *Int. J. Heat Mass Transf.*, **55-13-14** (2012), 3618–3632.
- 83) Kanaun, S. et al.: Conductive properties of foam materials with open or closed cells, *Int. J. Eng. Sci.*, **50-1** (2012), 124–131.
- 84) Andreozzi, A. et al.: Numerical analysis of radiation effects in a metallic foam by means of the radioactive conductivity model, *Appl. Therm. Eng.*, **49** (2012), 12–21.
- 85) Veyhl, C. et al.: On the thermal conductivity of sintered metallic fiber structures. *Int. J. Heat Mass Transf.*, **55-9-10** (2012), 2440–2448.
- 86) Zhou, W. et al.: Characterization of electrical conductivity of porous metal fiber sintered sheet using four-point probe method, *Mater. Des.*, **37** (2012), 161–165.
- 87) Fiedler, T. et al.: Critical analysis of the experimental determination of the thermal resistance of metal foams, *Int. J. Heat Mass Transf.* **55-15-16** (2012), 4415–4420.
- 88) Mancin, S. et al.: Foam height effects on heat transfer performance of 20ppi aluminum foams, *Appl. Therm. Eng.*, **49** (2012), 55–60.
- 89) Dygaa, R. et al.: Investigation of effective thermal conductivity aluminum foams, *Procedia Eng.*, **42** (2012), 1088–1099.

4. 応用

- 90) Nestic, S. et al.: Mechanical testing and finite element simulations for the use of cellular metals as car sheet components, *Steel Res. Int.*, **83-10** (2012), 972–980.
- 91) Huan, Z. et al.: Porous NiTi surfaces for biomedical applications, *Appl. Surf. Sci.*, **258-13** (2012), 5244–5249.
- 92) Maya, A. E. A. et al.: Zr–Ti–Nb porous alloys for biomedical application, *Mater. Sci. Eng. C*, **32-2** (2012), 321–329.
- 93) He, G. et al.: Porous titanium materials with entangled wire structure for load-bearing biomedical applications, *J. Mech. Behav. Biomed. Mater.*, **5-1** (2012), 16–31.
- 94) Ribeiro, G. B. et al.: Performance of microchannel condensers with metal foams on the air-side: Application in small-scale refrigeration systems, *App. Therm. Eng.*, **36** (2012), 152–160.

- 95) Zhang, H. et al.: Investigation of metallic foam in the application of turbine cooling, *Procedia Eng.*, **27** (2012), 752–761.