

1. 製法プロセス

1.1 溶湯法

- 1) Byakova, A. et al.: The role of foaming agent and processing route in mechanical performance of fabricated aluminum foams, *Procedia Mater. Sci.*, 4 (2014), 109-114.
- 2) Byakova, A. et al.: Fabrication method for closed-cell aluminium foam with improved sound absorption ability, *ibid.*, 4 (2014), 9-14.
- 3) Fukui, T. et al.: Fabrication of Al-Cu-Mg alloy foams using Mg as thickener through melt route and reinforcement of cell walls by heat treatment, *ibid.*, 4 (2014), 33-37.
- 4) 福井貴明ほか: A2024 と A7075 を用いた発泡材料の作製と気孔率や熱処理が機械的性質に及ぼす影響, *日本機械学会論文集*, 80 (2014), 1-9.
- 5) Szamel, G. et al.: Rheological behaviour of liquid ALUHAB aluminium foams, *Procedia Mater. Sci.*, 4 (2014), 75-79.
- 6) Babcsan, N. et al.: Pilot production and properties of ALUHAB aluminium foams, *ibid.*, 4 (2014), 127-132.
- 7) Garcia-Moreno, F. et al.: Analysis of liquid metal foams through X-ray radiography and microgravity experiments, *Soft Matter*, 10 (2014), 6955-6962.
- 8) Heim, K. et al.: The rupture of a single liquid aluminium alloy film, *Soft Matter*, 10 (2014), 4711-4716.
- 9) Yang, Q.Q. et al.: Pore structure of unidirectional solidified lotus-type porous silicon, *Trans. Nonferrous Met. Soc. China*, 24 (2014), 3517-3523.
- 10) Ide, T. et al.: Fabrication of porous copper with directional pores by continuous casting technique through thermal decomposition of hydride, *Metall. Mater. Trans.*, 45B (2014), 1418-1424.
- 11) Licavoli, J.L. et al.: Processing and pore growth mechanisms in aluminum Gasarites produced by thermal decomposition, *ibid.*, 45A (2014), 911-917.
- 12) Hayashida, T. et al.: Fabrication of porous aluminum alloys with aligned unidirectional pores by dipping pipes into liquid and semi-solid base metals, *Procedia Mater. Sci.*, 4 (2014), 82-86.
- 13) Sukanuma, K. et al.: Effect of ECAE on structure and strength of porous A6061 alloy with aligned unidirectional pores, *Key Eng. Mater.*, 622-623 (2014), 148-154.
- 14) Suzuki, S. et al.: Fabrication of porous aluminum alloys with aligned unidirectional pores by joining pipes and melt through continuous casting and their mechanical properties, *Procedia Mater. Sci.*, 4 (2014), 87-91.

1.2 粉末法

- 15) Lázaroa, J., et. al.: Heat treatment of aluminium foam precursors: effects on foam expansion and final cellular structure, *Procedia Mater. Sci.*, 4 (2014) 287-292.

- 16) Paulin, I.: Synthesis and characterization of Al foams produced by powder metallurgy route using dolomite and titanium hydride as a foaming agents, *Mater. and tech.*, 48 (2014) 943-947.
- 17) Shiomi, M., et al.: Forming of aluminum foams by using rotating mold, *Procedia Eng.*, 81 (2014) 664-669.
- 18) 半谷禎彦ほか: マルチパス摩擦粉末焼結法によるポーラスアルミニウム板の作製, *日本機械学会論文集*, DOI:10.1299/transjsme.14-00600.
- 19) Hangai, Y., et al.: Large-scale aluminum foam plate fabricated by enhanced friction powder compaction process based on sintering and dissolution process, *J. Mater. Proc. Technol.*, 214 (2014) 1721-1727.
- 20) 圖子田幸佑ほか: ツール走査型摩擦粉末焼結法によるポーラスアルミニウムの作製, *軽金属*, 64 (2014) 582-586.
- 21) 久森紀之: 初学者のためのバイオマテリアル I. バイオマテリアルの現状と応用, *材料*, 8 (2014) 1721-1727.

1.3 その他製作法・塑性加工・複合化

- 22) 秋田恵ほか: チェーンボール状鈴形 MHS 成形体の製造法および機械特性, 65回塑加連講論, (2014), 1-2.
- 23) Yoshimura H., et al.: Initial load of 'Kushidango' metallic hollow sphere structure under compression, *Procedia Mater. Sci.*, 4 (2014), 181-186.
- 24) 関野智之ほか: アルミニウム繊維焼結体を用いた衝撃吸収機構の開発, 65回塑加連講論, (2014), 17-18.
- 25) 中山昇ほか: 純アルミニウム繊維と純水の化学反応により成形した多孔質材料の機械的性質, 同上, (2014), 15-16.
- 26) 加藤公明ほか: 整形外科インプラント表面用チタン多孔体の研究, *日本機械学会2014年度年次大会講論* (2014), J0320301.
- 27) Murakami T., et al.: Development of porous iron based material by slag foaming and its reduction, *Procedia Mater. Sci.*, 4 (2014), 27-32.
- 28) Utsunomiya H., et al.: Deformation processes of porous metals and metallic foams (Review), *ibid.*, 4 (2014), 245-249.
- 29) Matsumoto R., et al.: Fabrication of nonporous layer on surface of ALPORAS by friction stir incremental forming, *ibid.*, 4 (2014), 239-243.
- 30) 金谷重宏ほか: レーザ積層造形による発泡アルミニウム表面への樹脂緻密層の形成, 65回塑加連講論, (2014), 9-10.
- 31) Hangai Y., et al.: Aluminum alloy foam core sandwich panels fabricated from die casting aluminum alloy by friction stir welding route, *J. Mater. Proc. Technol.*, 214-9 (2014), 1928-1934.
- 32) Duarte I., et al.: Dynamic and quasi-static bending behaviour of thin-walled aluminium tubes filled with

aluminium foam, *Comp. Struct.*, 109 (2014), 48-56.

- 33) Hangai Y., et al.: Fabrication of aluminum foam-filled thin-wall steel tube by friction welding and its compression properties, *Materials*, 7-9 (2014), 6796-6810.
- 34) He S.-Y., et al.: Preparation of density-graded aluminum foam, *Mater. Sci. Eng. A*, 618 (2014), 496-499.
- 35) Hangai Y., et al.: Fabrication and compression properties of functionally graded foam with uniform pore structures consisting of dissimilar A1050 and A6061 aluminum alloys, *ibid.*, 613 (2014), 163-170.

2. 機械的性質

2.1 実験的研究

- 36) 小川聡ほか: 炭酸水素ナトリウムによるポーラス Zn-22Al 超塑性合金の作製とそのセル形態, 平成26塑加春講論, (2014), 105-106.
- 37) 小川聡ほか: 炭酸水素ナトリウム粉末を用いて作製されたポーラス Zn-22Al 合金の圧縮特性, 65回塑加連講論, (2014), 19-20.
- 38) 石原綾乃ほか: 摩擦粉末焼結法によるポーラスアルミニウム合金の作製, 同上, (2014), 11-12.
- 39) Fei, Q., et al.: A Novel Way to prepare hollow sphere ceramics, *J. Am Ceram. Soc.*, 97-10 (2014), 3341-3347.
- 40) Santa M. J. A., et al.: Effect of hollow sphere size distribution on the quasi-static and high strain rate compressive properties of Al-A380-Al₂O₃ syntactic foams, *J. Mater. Sci.*, 49-3 (2014), 1267-1278.
- 41) Sheng, Z. et al.: Effect of scan line spacing on pore characteristics and mechanical properties of porous Ti6Al4V implants fabricated selective laser melting, *Mater. and Des.*, 63 (2014), 185-193.
- 42) Monika, K. et al.: Mechanical properties of porous Si₃N₄ ceramics, *Key. Eng. Mater.*, 586 (2014), 166-169.
- 43) 則武孝郁ほか: 軽量中空鋼球シートサンドイッチ構造体の曲げ特性に関する研究, 平成26塑加春講論, (2014), 109-110.
- 44) 則武孝郁ほか: 軽量中空鋼球シートサンドイッチ構造体の曲げ成形性の検討, 65回塑加連講論, (2014), 3-4.
- 45) Yoshida, Y., et al.: Development of metal hollow sphere sandwich construction and its formability and mechanical property, *Key. Eng. Mater.*, 611/612-2 (2014), 963-968.
- 46) 中野ゆき子ほか: ポーラスアルミニウムコア充填パイプにおける摩擦圧接の有効性, 65回塑加連講論, (2014), 13-14.

2.2 解析・シミュレーション

- 47) 桑水流理ほか: ポーラスアルミニウムのイメージベース有限要素解析とその精度検証, 軽金属, 64-11 (2014), 551-556.
- 48) 成瀬亘ほか: X線CTを用いたシミュレーション

フォーム/アルミニウムフォーム相互浸透複合材料の圧縮変形挙動の解析, 同上, 64-11 (2014), 598-603.

- 49) Niu, Z. et al.: Mesh generation of porous metals from X-ray computed tomography volume data, *J. Mech. Sci. Technol.*, 28-7 (2014), 2445-2451.
- 50) Amirirad, Y. et al.: Analysis of porosity-induced stress intensity factors for the evaluation of inline-computer tomography scans of cast parts, *Int. J. Adv. Manuf. Technol.*, 74-9-12 (2014), 1469-1485.
- 51) Kadkhodapour, J. et al.: Investigating internal architecture effect in plastic deformation and failure for TPMS-based scaffolds using simulation methods and experimental procedure, *Mater. Sci. Eng. C, Mater. Biol. Appl.*, 43 (2014), 587-597.
- 52) Winter, R.E. et al.: Plate-impact loading of cellular structures formed by selective laser melting, *Model. Simul. Mater. Sci. Eng.*, 22-2 (2014), 025021, 1-23.
- 53) Kim, K. et al.: Compliant cellular materials with compliant porous structures: a mechanism based materials design, *Int. J. Solids Struct.*, 51-23-24 (2014), 3889-3903.
- 54) Belhouideg, S. & Lagache, M.: Effects of the distribution and geometry of porosity on the macroscopic poro-elastic behavior: Compacted exfoliated vermiculite, *Int. J. Mech.*, 8-1 (2014), 223-230.
- 55) Yibin F., et al.: Sandwiched hollow sphere structures: A study of ballistic impact behavior using numerical simulation, *Proc. Inst. Mech. Eng. Part C*, 228-12 (2014), 2068-2078.

3. 熱, 電気, その他の性質

- 56) Mendes, M.A.A., et al: An improved model for the effective thermal conductivity of open-cell porous foams, *Int. J. Heat and Mass Trans.*, 75 (2014), 224-230.
- 57) Fiedler, T., et al: Determination of the thermal conductivity of periodic APM foam models, *ibid.*, 75 (2014), 826-833.
- 58) Pia, G. & Sanna, U.: An intermingled fractal units model to evaluate pore size distribution influence on thermal conductivity values in porous materials, *Appl. Therm. Eng.*, 65 (2014), 330-336.
- 59) Kumar, P., et al: Determination of effective thermal conductivity from geometrical properties: Application to open cell foams, *Int. J. Therm. Sci.*, 81 (2014), 13-28.
- 60) Ma, M.Y., & Ye, H.: An image analysis method to obtain the effective thermal conductivity of metallic foams via a redefined concept of shape factor, *Appl. Therm. Eng.*, 73 (2014), 1279-1284.
- 61) Mendes, M.A.A., et al.: Detailed and simplified models for evaluation of effective thermal conductivity of open-cell porous foams at high temperatures in

- presence of thermal radiation, *Int. J. Heat and Mass Trans.*, 75 (2014), 612-624.
- 62) Contento, G., et al.: The prediction of radiation heat transfer in open cell metal foams by a model based on the Lord Kelvin representation, *ibid.*, 75 (2014), 499-508.
- 63) Mendes, M.A.A.: Experimental validation of simplified conduction–radiation models for evaluation of Effective Thermal Conductivity of open-cell metal foams at high temperatures, *ibid.*, 75 (2014), 112-120.
- 64) Randrianalisoa, J. & Baillis: D., Thermal conductive and radiative properties of solid foams: Traditional and recent advanced modelling approaches, *Comptes Rendus Physique*, 15 (2014), 683-695.
- 65) Dietrich, B., et al.: Optical parameters for characterization of thermal radiation in ceramic sponges – Experimental results and correlation, *Int. J. Heat and Mass Trans.*, 75 (2014), 655-665.
- 66) Wulf, R., et al.: Experimental and numerical determination of effective thermal conductivity of open cell FeCrAl-alloy metal foams, *Int. J. Therm. Sci.*, 86 (2014), 95-103.
- 67) Antenucci, A., et al.: Improvement of the mechanical and thermal characteristics of open cell aluminum foams by the electrodeposition of Cu, *Mater. and Des.*, 59 (2014), 124-129.
- 68) Xiao, X., et al.: Effective thermal conductivity of open-cell metal foams impregnated with pure paraffin for latent heat storage, *Int. J. Therm. Sci.*, 81 (2014), 94-105.
- 69) Zhu, Y. et al.: Heat transfer measurements and correlation of refrigerant flow boiling in tube filled with copper foam, *Int. J. Refrigeration*, 38 (2014), 215-226.
- 70) Zaragoza, G., et al.: Development of a device for the measurement of thermal and fluid flow properties of heat exchanger materials, *Measurement*, 56 (2014), 37-49.
- 71) Pranoto, I., et al.: An experimental study of flow boiling heat transfer from porous foam structures in a channel, *Appl. Therm. Eng.*, 70 (2014), 100-114.
- 72) Mancin, S., et al, Liquid and flow boiling heat transfer inside a copper foam, *Procedia Mater. Sci.*, 4 (2014), 365-370.
- 73) Fernandez-Morales, P., et al.: A conceptual design of energy exchange system for recovery of residual heat using aluminum foams, *ibid.*, 4 (2014), 371-376.
- 74) Li, Y., et al.: Air flow resistance and sound absorption behavior of open-celled aluminum foams with spherical cells, *ibid.*, 4 (2014), 187-190.
- 75) Petrone, G. et al.: Numerical and experimental investigations on the acoustic power radiated by aluminium foam sandwich panels, *Comp. Struct.*, 118 (2014), 170-177.
- 76) Liu, S., et al.: Design optimization of porous fibrous material for maximizing absorption of sounds under set frequency bands, *Appl. Acoustic*, 76 (2014), 319-328.
- 77) Williams, P.T., et al.: Measurement of the bulk acoustic properties of fibrous materials at high temperatures, *ibid.*, 77 (2014), 29-36.
- 78) Leteller, M., et al.: Tortuosity studies of cellular vitreous carbon foams, *Carbon*, 80 (2014), 193-202.
- 5. ナノポーラス材料**
- 79) Kang, J. L. et al.: Self-grown oxy-hydroxide@nanoporous metal electrode for high-performance supercapacitors, *Adv. Mater.* 26-2 (2014), 269-272.
- 80) Hakamada, M. et al.: Photocatalysis of ZnO deposited on strained nanoporous Au, *Appl. Phys. A* 114-4 (2014), 1061-1066.
- 81) Hakamada, M. et al.: Fabrication of carbon nanotube/NiOx(OH)y nanocomposite by pulsed electrodeposition for supercapacitor applications, *J. Power Sources* 245 (2014), 324-330.
- 82) Zhang, P. et al.: ZIF-derived in situ nitrogen-doped porous carbons as efficient metal-free electrocatalysts for oxygen reduction reaction, *Energy Environ. Sci.* 7-1 (2014), 442-450.
- 83) Wada T. et al., Bulk-nanoporous-silicon negative electrode with extremely high cyclability for lithium-ion batteries prepared using a top-down process, *Nano Lett.* 14-8 (2014), 4505-4510.
- 6. 2次加工**
- 84) 菅沼光太郎ほか: ECAE 加工による方向性気孔を有するポーラスアルミニウム合金の強化と変形挙動, 平成26塑加春講演, (2014), 111-112.
- 85) Matsumoto, R. et al.: Fabrication of nonporous layer on surface of ALPORAS by friction stir incremental forming, *Procedia Mater. Sci.*, 4(2014), 239-243.
- 86) Kanatani, S., et al.: H.: Filling of pores of aluminum foam surface with aluminum powder by selective laser melting, *Key Eng. Mater.*, 622-623 (2014), 861-867.
- 87) 金谷重宏ほか: レーザ積層造形による発泡アルミニウム表面への樹脂緻密層の形成, 65回塑加連講論, (2014), 9-10.
- 88) Takekoshi, I., et al.: Deformation behavior in die forging of aluminum foam sandwich, *Procedia Eng.*, 81 (2014), 564-567.
- 89) Mata, H., et al.: Study on the forming of sandwich shells with closed-cell foam cores, *Int. J. of Mater. Form.*, 7-4 (2014), 413-424.
- 90) 田口裕規ほか: 摩擦攪拌法によって作製したポーラスアルミニウム/アルミニウム板サンドイッチパネルの曲げ試験, 日本機械学会2014年度年次大会 DVD 講演論文集, (2014), J0320304 (3 pages).
- 91) 久保田直之ほか: A1050と ADC12を用いた複合ポーラス Al の衝撃圧縮特性評価, 同上, (2014), J0320203.

- 92) Shiomi, M., et al.: Influence of gravity and mold shape on molding of aluminum foams, *Adv. Mater. Research*, 875-877 (2014), 1280-1284.
- 93) Cambrono, et al.: Weld structure of joined aluminium foams with concentrated solar energy, *J. Mater. Proc. Technol.*, 214-11(2014), 2637-2643.
- 94) Quadrini, F., et al.: Numerical simulation of laser forming of aluminum sponges: Effect of temperature and heat treatments, *Key Eng. Mater.*, 611-612(2014), 981-988.